

# Murray

## WHY USE A SINGLE MAGNETIC LOCK OR STRIKE?

### SPECIFICATION SHEET FOR 8000 SERIES PANIC DEVICE



**Check out our pricing section and save big on rim panic bars.**

#### FEATURES

- ◆ Grade 1 UL listed for electrically control panic device
- ◆ Bar can be dogged electrically or mechanically
- ◆ Comes Fail Secure. No battery back up needed to remain locked. Meets new Life Safety Code.
- ◆ Installs in less than 45 minutes average time.
- ◆ Comes with full templates for easy installation.
- ◆ Very low power draw. No special booster needed
- ◆ Meets requirements for being tied into life safety system and mechanical action for exit.
- ◆ Can be shipped with a built in REX switch for Request to Exit
- ◆ Available in 36 and 48 inches
- ◆ Available in Duranotic and Aluminum
- ◆ Comes with self drilling self tapping installation screws
- ◆ Available in 12 or 24 volt AC/DC. Each bar has a built in Full Wave Bridge Rectifier for AC/DC use

- ◆ UL listed under control number 24RK.
- ◆ Unlike a Magnetic lock, you can use a key
- ◆ Fail Secure operation means no battery back up.
- ◆ Patented design meets new Life Safety Code
- ◆ Very low current draw. Only .300 amp @ 24V
- ◆ Comes with full template and instructions
- ◆ All surface mounted. No cutting of frame or door.
- ◆ Comes with self drilling, self tapping screws.
- ◆ No special power supply or booster required.
- ◆ Available for wood, metal and aluminum doors.
- ◆ Continuous duty to allow for electric dogging.

SEE PRICING SHEET FOR SPECIFICATION AND ORDERING INFORMATION