



- Proven effective for more than a decade in helping stop false fire alarms without restricting legitimate alarms
- Fits virtually all manual pull stations, larger sizes and surface mounted pull stations accommodated with STI 3100 conduit spacer
- Tested and accepted by fire prevention authorities and approved by testing organizations
- Cover is UV stabilized against sun deterioration
- Available in red, blue, green or yellow with custom labeling
- Unconditional lifetime guarantee of the Stopper II molded polycarbonate cover against breakage and damage
- Can be used as a guard against physical damage to a manual pull station, with or without a warning horn
- Weather resistant gaskets available. UL requires stations be listed for outdoor use with cover
- Power source is 9 VDC alkaline battery on standard Stopper II (Remote powered unit is available)

Patent Approvals: United States No. 4267549, Canada No. 1147828Z

This unique and patented device has been helping stop false fire alarms without restricting legitimate alarms for more than a decade. Proven use in virtually every kind of public building around the world, Stopper II can dramatically reduce, or in some cases, even eliminate false fire alarms. Available in many different models: with or without warning horn, flush or surface mount, and with remote power relay output capability. Stopper II may be ordered in your choice of red, green, yellow or blue with custom labeling for specialized applications.

Stock Number	Model Number	Description
1000173	STI 1100	With horn, flush mount
N/S	STI 1130	With horn, spacer for surface mounting
1000172	STI 1200	Without horn, flush mount
N/S	STI 1230	Without horn, spacer for surface mounting
1000174	STI 3100	2" clear conduit spacer for surface mounting. May be stacked for additional depth.

