

BPU-350SATA

3 to 5 SATA II Raid Back-Plane



INTRODUCTION

High level Raid and high availability storage in compact design, BPU-350 add extra storage and hot-swap capability to satisfy any application needs. The BPU is constructed of aluminum material that provides best heat dissipation required for high performance SATA drives, is designed with excellent front to back vent airflow. The BPU series is an ideal solution for internal server RAID and JBOD applications. Aluminum body and extra 80mm cooling fan subsystem complete a high end data storage server or workstation.

FEATURES

- Ⓐ Heavy-Duty Aluminum with Advanced Structure Compact Design
- Ⓑ Support Plug & Play and Hot-Swappable Tray
- Ⓒ SATA I or II Compatible (Transfer rate up to 3.0 Gbp/s)
- Ⓓ 8cm Fan Provides Excellent Air Ventilation & Heat Sink
- Ⓔ Power Control Switch, Sensor, Alarm & Reset
- Ⓕ Built-in LED for Monitoring P/S and Temperature Overheat
- Ⓖ Safety Tri-angle Lock for HDD
- Ⓗ SATA 15 Pin & 4 Pin Power Connectors
- Ⓘ Patent Balance Handle - No Skew In/Out
- ⓵ RoHS Compliant

SPECIFICATION

MODEL NO.	BPU-350SATA (Rhino RJ Series)
DRIVE BAYS	3 x 5.25" to 5 x3.5"
INTERFACE	SATA 2.0 Hot-Swap Capable
COOLING	1 x 80mm Ball Bearing Fan
MATERIAL	All Aluminum Design
DIMENSIONS (WxDxH)	126 x 206 x 146 (mm)
POWER CONNECTOR	Power SATA 15pin x 2, 4pin x 3
SCSI ID	SATA Cable Included (5pcs)
WEIGHT	7lbs
FAN FAILURE SENSOR	Buzzer Alarm (3 Stage) Overheating Alarm (50/60/65)

